

ThinkPad X390 Yoga Platform Specifications

Product Specifications Reference (PSREF)

Processor	8th Generation Intel® Core™ i5 / i7 Processor								Smart card reader Media reader Ports	Optional: Smart card reader MicroSD card reader, in the combo slot with nano-SIM card Two USB 3.1 Gen 1 (one Always On), one USB 3.1 Type-C Gen 1 (with the function of Power Delivery and Display Port), one USB 3.1 Type-C Gen 2 / Thunderbolt 3 (with the function of PD and DP), HDMI 1.4b, Ethernet extension connector, combo slot of nano-SIM card (WWAN models) and microSD card reader, headphone / microphone combo jack, optional smart card reader, side docking connector, security keyhole * Depending on many factors, actual data transfer speed may be lower than theoretical speed
	Processor Number	# of Cores	# of Threads	Base Frequency	Max Turbo Frequency	Cache	Memory Types	Processor Graphics		
	i5-8265U	4	8	1.6 GHz	3.9 GHz	6MB	DDR4-2400	Intel UHD Graphics 620		
	i5-8365U	4	8	1.6 GHz	4.1 GHz	6MB				
	i7-8565U	4	8	1.8 GHz	4.6 GHz	8MB				
i7-8665U	4	8	1.9 GHz	4.8 GHz	8MB					
Graphics	Intel UHD Graphics 620 in processor only; supports external digital monitor via HDMI or USB Type-C; supports three independent displays; Max resolution: 4096x2304 @60Hz (USB Type-C); 4096x2160 @24Hz (HDMI)								Monitor cable (optional)	USB-C to HDMI: Lenovo USB-C to HDMI Adapter USB-C to VGA: Lenovo USB-C to VGA Adapter USB-C to DP: Lenovo USB-C to DisplayPort Adapter
Chipset	Intel SoC (System on Chip) platform								Bundled Accy	Optional: ThinkPad Ethernet Extension Adapter Gen 2
Memory	8GB or 16GB / 2400MHz DDR4 / soldered to systemboard, no sockets * Installed memory is actually 2666MHz but run at 2400MHz due to Intel limitation								Camera	One of the following, configurable by model: • HD720p camera, with ThinkShutter camera privacy, fixed focus • IR camera and HD720p camera, with ThinkShutter camera privacy, fixed focus
Display	13.3" (337.8mm) FHD (1920x1080), LED backlight, IPS, Glossy, 300 nits, 16:9 aspect ratio, 800:1 contrast ratio, Color Gamut 72%, 170° viewing angle, capacitive-type multi-touch, AR (anti-reflection), AS (anti-smudge)								Audio support	HD Audio, Realtek® ALC3287 codec / stereo speakers, 2W x 2, Dolby® Audio™ Premium / dual array microphone, headphone / microphone combo jack
Multi-touch	supports 10-finger gesture								Keyboard	6-row, spill-resistant, multimedia Fn keys, LED backlight
Hinge	Yoga hinge, 360 degree								UltraNav™	TrackPoint® pointing device and buttonless Mylar surface multi-touch touchpad
Convert-mode	Laptop, tent, stand and tablet								Security	Power-on password, hard disk password, supervisor password, security keyhole
Pen	ThinkPad Pen Pro, active pen for multi-touch display, on-board rechargeable								Security chip	Discrete TPM 2.0 TCG Certified
Storage	<ul style="list-style-type: none"> M.2 2280 SSD / SATA 6.0Gb/s M.2 2280 SSD / PCIe NVMe, PCIe 3.0 x 4 M.2 2242 SSD / PCIe NVMe, PCIe 3.0 x 2 								vPro (optional)	Intel vPro Technology
Optane™ memory	Intel Optane memory, PCIe NVMe, PCIe 3.0 x 2								Fingerprint reader	Touch style match on chip fingerprint reader on the palm rest
Optical	None								NFC (optional)	Near Field Communication
Ethernet	Native Intel Ethernet Connection I219-V (Non-vPro) or I219-LM (vPro) via bundled or optional ThinkPad Ethernet Extension Adapter Gen 2								Battery	Integrated Li-ion 50Wh battery, supports Rapid Charge (charge up to 80% in 1hr) with 65W USB Type-C AC adapter
WLAN	<i>One of the following, configurable by model:</i> <ul style="list-style-type: none"> Intel Wireless-AC 9560, Wi-Fi 2x2 802.11ac + Bluetooth 5.0 Intel Wi-Fi 6 AX200, Wi-Fi 2x2 802.11ax + Bluetooth 5.0 								Max battery life	MobileMark® 2014: 14.5 hrs * Battery life varies significantly with settings, usage, & other factors
Bluetooth™	Bluetooth 5.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter								AC adapter	45W or 65W USB Type-C AC adapter
WWAN (optional)	<i>One of the following, configurable by model:</i> <ul style="list-style-type: none"> Integrated Mobile Broadband 4G LTE, Fibocom L830-EB, M.2 card (EMEA only) Integrated Mobile Broadband 4G LTE-A, Fibocom L850-GL, M.2 card * For non-WWAN model, it means the model is NOT WWAN upgradable								Light sensor	None
Dimensions	WxDxH: 12.22" x 8.62" x 0.63"; 310.4mm x 219mm x 15.95mm								G-sensor	3D accelerometer
Weight	Starting at 2.85 lb (1.29kg)								Gyroscope	3D gyrometer
Case color	Black or silver								Preload	Windows® 10 Home 64 or Windows 10 Pro 64
Case Material	Display cover: Carbon-Fiber Hybrid Bottom: Carbon-Fiber Hybrid								Limited warranty	<i>One of the following, configurable by model:</i> <ul style="list-style-type: none"> 1-year depot repair service 3-year/1-yr battery depot repair service 3-year/1-yr battery limited onsite service
									Mil-Spec test	MIL-STD-810G military certification
									Environment	EPEAT™ Bronze; ENERGY STAR® 7.0; RoHS-compliant